

Appl. No. 09/981,789  
Amdt. Dated December 1, 2003  
Reply to Office action of October 1, 2003  
Attorney Docket No. P13685-US1  
EUB/J/P/03-2014

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Previously Presented) A device (1) for transmitting or receiving electromagnetic waves in a cavity (3), comprising a loop (10) and a dielectric part (9) that houses at least a first end part (11) of the loop (10), where the dielectric part (9) defines a first recess (37) arranged to receive a means (30) for setting the capacitance between the loop (10) and a grounded casing (2), cavity housing (5) or cover (6) and where the loop (10) is embedded in the dielectric part (9) at the first end part (11), and wherein the loop (10) comprises a flat section that is designed for a predetermined frequency.

2-4. (Cancelled).

5. (Currently Amended) A device (1) according to Claim 1, where the dielectric part (9) comprises a bottom surface of the first recess, said bottom surface covers the flat section from a first direction, in order to prevent the means (30) for setting the capacitance from coming into galvanic contact with the loop (10) and to prevent electrical flash-over between the loop (10) and the means (30) for setting the capacitance.

6. (Previously Presented) A device (1) according to Claim 5, where the dielectric part (9) comprises a second recess (48) on an opposite side of the dielectric

Appl. No. 09/981,789  
Amdt. Dated December 1, 2003  
Reply to Office action of October 1, 2003  
Attorney Docket No. P13685-US1  
EUS/J/P/03-2014

part to the first recess (37), with a bottom surface that covers the flat section from an opposite direction to the first direction.

7. (Currently Amended) A device (1) according to Claim 1, where the first end part (11) has an essentially straight longitudinal axis and the first recess (37) is turned essentially at right angles to ~~this~~ the longitudinal axis.

8. (Cancelled).

9. (Previously Presented) A device (1) according to Claim 1, comprising at least one rib (40) inserted in the first recess (37) to make contact with the means (30) for setting the capacitance.

10. (Original) A device (1) according to Claim 1, comprising at least one stop pin (41) projecting into the first recess (37) in order to prevent the means (30) for setting the capacitance from coming into galvanic contact with the loop (10) and to prevent electrical flash-over between the loop (10) and the means (30) for setting the capacitance.

11. (Original) A device (1) according to Claim 1, where the dielectric part (9) houses a second end part (13) of the loop (10).

12. (Currently Amended) A device (1) according to Claim 11, where the second end part (13) is ~~essentially~~ substantially parallel to the first end part (11).

Appl. No. 09/981,789  
Amdt. Dated December 1, 2003  
Reply to Office action of October 1, 2003  
Attorney Docket No. P13685-US1  
EUS/J/P/03-2014

13. (Currently Amended) A device (1) according to Claim 11, where at least one of the first end part (11) and the second end part (13) is milled in order to ~~provide good fixing of~~ securely fix the loop (10) in the dielectric part (9).

14. (Previously Presented) A device (1) according to Claim 11, where the dielectric part (9) is designed to provide a particular impedance to the grounded casing (2), cavity housing (5) or cover (6), together with the loop (10).

15. (Original) A device (1) according to Claim 1, where the dielectric part (9) comprises a locking device (23).

16. (Currently Amended) A device (1) according to Claim 1, where the dielectric part (9) comprises a ~~fixing~~ hole (29) designed to receive ~~[[a]]~~ an ~~fixing~~ element ~~for fixing to~~ securely fix the device (1) to the casing (2), cavity housing (5) or cover (6).

17. (Original) A device (1) according to Claim 1, where the dielectric part (9) comprises at least one second recess (38).

18 - 24. (Cancelled).